

# TPE SEALER SYSTEM

## VANTE® WELDER & SEALER

The all-new Vante® 4160-series TPE Tubing Sealer is the obvious choice for the reliable, efficient creation of permanent seals in thermoplastic tubing common in single-use manufacturing procedures performed in biopharmaceutical cleanroom production suites, allowing for ease of separation at the seal area. It operates with voltage rated inputs of 100-120 VAC or 230 VAC. The connection of an external compressed air supply is not required. Offering the ultimate in portability, this tubing sealer can be easily moved throughout the suite. The durable, maintenance-free sealing heads are connected to the controller with an 8ft cable and are equipped with a remote cycle-start feature to make this the only TPE Sealer offered standard with truly remote tube sealing capabilities. The controller is equipped with 2 levels of password protection for quality assurance and process control. A simple, user-friendly control panel allows for accurate configuration and operation. The sealing heads have a built-in safety lock feature to prevent them from being opened once a sealing cycle has been initiated. This all-new Vante TPE Tubing Sealer consists of the Model 4160 Controller and interchangeable sealing heads - Model 4161 Sealing Heads for thin-wall TPE tubing, and Model 4162 Sealing Heads for thick-wall TPE tubing up to 1-inch outside diameter.

### Controller Model 4160

#### Thin-Wall Sealing Head Model 4161

This sealing head model seals .062 & .094 inch wall thickness tubing with an outside diameter range of .250 to .688 inches.

#### Thick-Wall Sealing Head Model 4162

This sealing head model seals .125 inch wall thickness tubing with an outside diameter range of .375 to 1.00 inches.

### Features:

- Password protected settings
- Standard remote sealing heads with safety lock and cycle start button
- Increased tubing O.D. capability to 1"

### Benefits:

- No external compressed air required
- Truly remote sealing capability
- Settings are easily adjusted and locked
- Ease of operation
- Very low maintenance
- Easy to clean



# TPE SEALER SYSTEM

## MECHANICAL SPECIFICATIONS

	4160	4160	4162
Dimensions (W x L x H)	9 x 16.5 x 6 inches 22.5 x 41 x 15 cm	3 x 12.5 x 2 inches 7.5 x 31.5 x 5 cm	3 x 13 x 2 inches 7.5 x 32.5 x 5 cm
Operating Weight	14 lbs (5.4 kg)	2.5 lbs (1.13 kg)	2.6 lbs (1.18 kg)

## ELECTRICAL SPECIFICATIONS

	4160	4160	4162
Certifications	cTUVus, CE, WEEE, RoHS		
Power Input	100VAC +/-10%, 50-60Hz 115VAC +/-10%, 50-60 Hz 230VAC +/- 10%, 50-60 Hz	100VAC +/-10%, 50-60Hz 115VAC +/-10%, 50-60 Hz 230VAC +/- 10%, 50-60 Hz	100VAC +/-10%, 50-60Hz 115VAC +/-10%, 50-60 Hz 230VAC +/- 10%, 50-60 Hz
Main Fuses	(100VAC units) 4A (115VAC units) 4A (230VAC units) 2A		

## PERFORMANCE FACTORS

	4160	4160	4162
Tubing Sizes (O.D.)		.250 - .688 inches .062 & .094 inch wall thickness	.375 - 1.00 inches .125 inch wall thickness

## OPERATING CONDITIONS

	4160	4160	4162
Temperature	59°-95° F (15°-35°C)	59°-95° F (15°-35°C)	59°-95° F (15°-35°C)
Humidity	70% maximum relative humidity (non-condensing)	70% maximum relative humidity (non-condensing)	70% maximum relative humidity (non-condensing)
Compressed Air Supply	Not Required		



**TECNO PLAST**  
INDUSTRIE-TECHNIK GMBH

Willstätterstr. 5 · 40549 Düsseldorf · Tel. 0211/53 74 33-0 · Fax 0211/59 39 14 · [www.tecnoplast.de](http://www.tecnoplast.de)